

CS181: Computer Vision

Image Segmentation

Clustering-based segmentations (k-means, mean-shift, SLIC)

Thursday, October 15th, 2026



Md Alimoor Reza

Associate Professor of Computer Science


Today's agenda

- Image Segmentation
- Image Segmentation Approaches
 - Algorithmic approach
 - Learning-based approach

Image segmentation



- **Goal:**

- break apart an image into simpler components
- reduce an image to a small number of homogeneous regions (“segments”)



Hard to judge success


- Which of these segmentations is “correct”?



[Martin 2001]

Image segmentation



- Goal: identify groups of pixels that go together.



The goals of segmentation

- Separate image into coherent “objects”
- Group together ***similar-looking*** pixels for efficiency of further processing
 - How can you measure similarity?

superpixels




X. Ren and J. Malik. [Learning a classification model for segmentation](#). ICCV 2003.

Source: Lana Lazebnik

What is Similarity?

The quality or state of being similar; likeness; resemblance; as, a similarity of features.

Webster's Dictionary



Similarity is hard to define, but...
"We know it when we see it"



The real meaning of similarity is a philosophical question. We will take a more pragmatic approach.

Slide by E. Keogh


Today's agenda

- Image Segmentation
- Image Segmentation Approaches
 - Algorithmic approach
 - Clustering-based algorithms
 - Graph-based algorithms
 - Learning-based approach


Image segmentation: toy example




- Three intensities define the three groups.
- We could label every pixel in the image according to its greyscale value.




input image



What to do when there is noise in our data?




input image



Today's agenda

- Image Segmentation
- Image Segmentation Techniques
 - Algorithmic approach
 - Clustering-based algorithms
 - k-means clustering
 - Graph-based algorithms
 - Learning-based approach



- **Goal:** choose 3 “centers” as representative intensities, label each pixel according to which center is nearest.
- Best cluster centers minimize sum squared difference between each point and its nearest cluster center c_i :

Objective function


minimize

$$\sum_{\text{clusters } i} \sum_{\text{points } p \text{ in cluster } i} \|p - c_i\|^2$$


Similarity measure:
Euclidean distance

A chicken and egg problem

- If we knew the **cluster centers**, we could allocate points to groups by assigning each to its closest center.




- If we knew the **group memberships**, we could get the centers by computing the mean per group.



K-means clustering

- **Basic idea**: randomly initialize the k cluster centers, and iterate between the two steps we just saw.

1. Randomly initialize the cluster centers, $c_1, \dots, c_K$
2. Given cluster centers, determine points in each cluster
 - For each point p , find the closest c_i . Put p into cluster i
3. Given points in each cluster, solve for c_i
 - Set c_i to be the mean of points in cluster i
4. If c_i have changed, repeat Step 2



- **Properties**

- Will always converge to *some* solution
- Might be a local minimum; i.e. not a global minimum of:


K-means

1. Randomly initialize the cluster centers, $c_1, \dots, c_K$




K-means

1. Randomly initialize the cluster centers, $c_1, \dots, c_K$
2. Given cluster centers, determine points in each cluster




K-means

1. Randomly initialize the cluster centers, $c_1, \dots, c_K$
2. Given cluster centers, determine points in each cluster
3. Given points in each cluster, solve for c_i




K-means

1. Randomly initialize the cluster centers, $c_1, \dots, c_K$
2. Given cluster centers, determine points in each cluster
3. Given points in each cluster, solve for c_i




K-means

1. Randomly initialize the cluster centers, $c_1, \dots, c_K$
2. Given cluster centers, determine points in each cluster
3. Given points in each cluster, solve for c_i



K-means

1. Randomly initialize the cluster centers, $c_1, \dots, c_K$
2. Given cluster centers, determine points in each cluster
3. Given points in each cluster, solve for c_i



If we run it for enough iterations, it will converge to this state, when the centers won't be changing anymore. Clustering mechanism stops.

Segmentation as clustering

We can customize the clustering by changing the feature space.

e.g. Grouping pixels based on intensity similarity






K=2





K=3



Segmentation as clustering


e.g. Grouping pixels based on color similarity



Feature space: color value (3-d)



Smoothing out cluster assignments


- Assigning a cluster label per pixel may yield outliers:




Segmentation as clustering

e.g. Grouping pixels based on intensity+position similarity







Clustering pixels based
on color alone



Clustering pixels based
on color and position

Segmentation as clustering

e.g. Grouping pixels based on texture similarity



Filter bank of
24 filters


K-means: pros and cons

Pros


- Simple, fast to compute
- Converges to local minimum of within-cluster squared error

Cons/issues


- Setting k ?
- Sensitive to initial centers
- Sensitive to outliers
- Detects spherical clusters




(A): Undesirable clusters



(B): Ideal clusters



(A): Two natural clusters



(B): k -means clusters

Today's agenda

- Image Segmentation
- Image Segmentation Approaches
 - Algorithmic approach
 - Clustering-based algorithms
 - k-means clustering
 - mean-shift clustering
 - Graph-based algorithms
 - Learning-based approach

Mean Shift: Object Proposal Generation in 3D point cloud

Multiview RGB-D Dataset for Object Instance Detection

Georgios Georgakis, Md Alimoor Reza, Arsalan Mousavian, Phi-Hung Le, Jana Košecká

Department of Computer Science

George Mason University

{ggeorgak,mreza,amousavi,ple13,kosecka}@gmu.edu

Abstract

This paper presents a new multi-view RGB-D dataset of nine kitchen scenes, each containing several objects in realistic cluttered environments including a subset of objects from the BigBird dataset [26]. The viewpoints of the scenes are densely sampled and objects in the scenes are annotated with bounding boxes and in the 3D point cloud. Also, an approach for detection and recognition is presented, which is comprised of two parts: i) a new multi-view 3D proposal generation method and ii) the development of several recognition baselines using AlexNet [14] to score our proposals, which is trained either on crops of the dataset or on synthetically composited training images. Finally, we compare the performance of the object proposals and a detection baseline to the Washington RGB-D Scenes (WRGB-D) dataset [15] and demonstrate that our Kitchen scenes dataset is more challenging for object detection and recognition. The dataset is available at: <http://cs.gmu.edu/~robot/gmu-kitchens.html>.

1. Introduction




Figure 1: Top left: Example reconstructed scene from the Kitchen scenes dataset. Top right: Generation of 3D object proposals using a simple clustering algorithm. Bottom left: Proposals projected on a 2D image in the scene. For clarity only proposals with high overlap with the ground truth are shown. Bottom right: Object recognition using our projected proposals. The blue bounding boxes are the ground truth, the green are correct detections, and the red are false detections.

Multiview RGB-D dataset for object instance detection

G Georgakis, MA Reza, A Mousavian, PH Le, J Košecká

2016 Fourth International Conference on 3D Vision (3DV), 426-434

Mean Shift: Object Proposal Generation in 3D point cloud



Figure 4: 3D Object proposal generation: (a) Dense point cloud of a scene; (b) output of the plane detection algorithm; (c) output of the Mean Shift clustering given $radius = 0.4$ after removing 33% of the large planes; (d) extracted 3D proposals after cuboid fitting.

Today's agenda


- Image Segmentation
- Image Segmentation Approaches
 - Algorithmic approach
 - Clustering-based algorithms
 - k-means clustering
 - mean-shift clustering
 - SLIC clustering
 - Graph-based algorithms
 - Learning-based approach

Simple Linear Iterative Clustering (SLIC)

- SLIC clusters pixels in the combined five-dimensional color and image plane space to generate compact, nearly uniform segments (also called superpixels)
- Very fast, can generate superpixels in less than a second.




RGB



SLIC superpixels

Simple Linear Iterative Clustering (SLIC)




SLIC superpixels with different parameters

Segmentation by Reza et al. RSSw'2014


- Utilize the depth information to find dominant planar surfaces by fitting planes¹ from 3D points
- represent remaining as compact² regions in 2D image space



SLIC segmentation on RGB image



plane extraction from depth image



Color coded segmentation


Activity: Clustering-based Segmentation

▼ SLIC clustering based algorithm

- `n_segment` -- (approximate) number of labels in the segmented output image.
- `compactness` -- balances color proximity and space proximity


```
[ ] from skimage.segmentation import slic
    #img = skimage.io.imread('data/'+image_names[1])
    img = coffee()
    # ----- SLIC -----
    segments = slic(img, n_segments=200, compactness=10, sigma=1)
    plt.imshow(np.asarray(segments))
    plt.imshow(mark_boundaries(img, segments))
    plt.title('SLIC clustering-based segmentation')
```

Text(0.5, 1.0, 'SLIC clustering-based segmentation')



Recognition through segmentation

- Many vision systems have tried to use segmentation as an intermediate step, e.g.
 - Do segmentation on an image
 - Compute features (shape, color, etc.) for each segment
 - Decide whether each segment is an object or not



Segmentation: Caveats

- Image segmentation is not a bottom-up problem
 - Needs to be done with recognition, simultaneously
- Segmentation makes hard decisions
 - Making the wrong decision could be catastrophic for later steps of a system
- Difficult to evaluate; when is a segmentation successful?

